

MICROMINI

Walk Behind Scrubber Specifications



MICROMINI 20" (51 cm)

MICROMINI 24" (61 cm)

BODY CONSTRUCTION / DIMENSIONS:

Tank Material:	Poly (5/16" thick) (.79375 cm)	Poly (5/16" thick) (.79375 cm)
Chassis Construction:	3/16" Coated Steel (.47625 cm)	3/16" Coated Steel (.47625 cm)
Rear Casters:	(2) 2.5" x 1.38" [(2) 6.35 x 3.5 cm]	(2) 2.5" x 1.38" [(2) 6.35 x 3.5 cm]
Front Wheels:	(2) 8" x 2" [(2) 20 x 8 cm]	(2) 8" x 2" [(2) 20 x 8 cm]
Size (L x W x H):	42" x 21" x 39" (106 x 53 x 99 cm)	42" x 21" x 39" (106 x 53 x 99 cm)
Weight (w/o batteries)	265 lbs (69 kg)	265 lbs (69 kg)
Weight (w/batteries)	430 lbs (144 kg)	430 lbs (144 kg)

BRUSH SYSTEM:

Edge Pad Size:	20-Edge: (1) 20" x 14"	24-Edge: (1) 24" x 14"
Edge Pad Motor	(1) 1.0 hp (895 watts)/ 2500 rpm	(1) 1.0 hp (895 watts)/ 2500 rpm
Optional Brush Motor	(1) 1.2 hp (895 watts)/ 2900 rpm	(1) 1.2 hp (895 watts)/ 2900 rpm
Brush Down Pressure:	0 - 125 lbs (0-68 kg)	0 - 125 lbs (0-68 kg)

BATTERY SYSTEM:

System Voltage	24 volts	24 volts
Standard Battery Rating:	130 ah	130 ah
Optional Battery Rating:	Up to 150 ah	Up to 150 ah
Battery Run Time:	Up to 3 hours	Up to 3 hours
Charger (110-v / 60 Hz / 24-volt):	12 amp Dual Mode Console	12 amp Dual Mode Console

SOLUTION SYSTEM:

Solution Tank Cap.:	10 gallons (38 liters)	10 gallons (38 liters)
Solution Flow Rate:	0 - .5 gpm (0 - 2 lpm)	0 - .5 gpm (0 - 2 lpm)
Solution Filter:	Stainless / Inline	Stainless / Inline

RECOVERY SYSTEM:

Recovery Tank Cap.:	10 gallons (38 liters)	10 gallons (38 liters)
Vac. Power:	0.75 hp (559 watts)	0.75 hp (559 watts)
Drain Hose:	1.5" diameter (4 cm)	1.5" diameter (4 cm)
Vacuum Specs (lift / airflow):	70" / 70 cfm (178 cm / 21 cmm)	70" / 70 cfm (178 cm / 21 cmm)
Demisting Chamber:	1.25 gallons (5 liters)	1.25 gallons (5 liters)
Drain Saver:	30 cubic inches (70 cubic cm)	30 cubic inches (70 cubic cm)

GENERAL:

Cleaning Width:	20-E: 20" (51 cm)	24-E: 24" (61 cm)
Cleaning Rate/Hour (Sq.Ft/Hr):	Up to 18,474 (5,631 m)	Up to 20,525 (6,256 m)
Sound Level:	67 dBA	67 dBA

DRIVE SYSTEM:

Standard Drive:	0.75 hp (559 watts), all gear / sealed	0.75 hp (559 watts), all gear / sealed
Forward Speed:	0-230 ft/min (4 mph) (6 kph)	0-230 ft/min (4 mph) (6 kph)
Reverse Speed:	0-130 ft/min (2 mph) (3 kph)	0-130 ft/min (2 mph) (3 kph)

RPS CORPORATION

P.O. Box 368
Racine, WI 53401
Phone: (800) 634-4060
Fax: (866) 901-3335

© RPS Corporation 2013.
All Rights Reserved.

Since our policy is one of constant improvement,
all specifications are subject to change without notice.

AUTHORIZED DISTRIBUTOR