

MICROMAG

Walk Behind Scrubber Specifications



MICRO 17", 20" (43, 51 cm)

MICROMAG 17" , 20" (43, 51 cm)

BODY CONSTRUCTION / DIMENSIONS:

| | | |
|------------------------|--------------------------------------|--------------------------------------|
| Tank Material: | Poly (5/16" thick) (.79375 cm) | Poly (5/16" thick) (.79375 cm) |
| Chassis Construction: | 1/8" Coated Steel (.3175 cm) | 1/8" Coated Steel (.3175 cm) |
| Rear Wheels: | (2) 8" x 2" [(2) 20 x 5 cm] | (2) 8" x 3" [(2) 20 x 8 cm] |
| Front Casters: | (2) 2.5" x 1.38" [(2) 6.35 x 3.5 cm] | (2) 2.5" x 1.38" [(2) 6.35 x 3.5 cm] |
| Size (L x W x H): | 35" x 18" x 38" (89 x 46 x 97 cm) | 38" x 18" x 38" (89 x 46 x 97 cm) |
| Weight (w/o batteries) | 115 lbs (52 kg) | 152 lbs (69 kg) |
| Weight (w/batteries) | 298 lbs (135 kg) | 317 lbs (144 kg) |

BRUSH SYSTEM:

| | | |
|----------------------|--|--|
| Disk Brush/Pad Size: | 17-D: (1) 17" (43 cm) 20-D: (1) 20" (51 cm) | 17-D: (1) 17" (43 cm) 20-D: (1) 20" (51 cm) |
| Disk Brush Motor | (1) .75 hp (559 watts)/ 200 rpm | (1) .75 hp (559 watts)/ 200 rpm |
| Optional Brush Motor | (1) .75 hp (559 watts)/ 200 rpm | (1) .75 hp (559 watts)/ 200 rpm |
| Brush Down Pressure: | 0 - 75 lbs (0-34 kg) | 0 - 125 lbs (0-68 kg) |
| Edge Pad Size: | NA | 20-Edge: (1) 20" x 14" |
| Edge Pad Motor | NA | (1) 1.0 hp (780 watts)/ 2500 rpm |

BATTERY SYSTEM:

| | | |
|------------------------------------|-------------------------|-------------------------|
| System Voltage | 24 volts | 24 volts |
| Standard Battery Rating: | 85 ah | 85 ah |
| Optional Battery Rating: | up to 130 ah | up to 130 ah |
| Battery Run Time: | Up to 3 hours | Up to 3 hours |
| Charger (110-v / 60 Hz / 24-volt): | 8 amp Dual Mode Console | 8 amp Dual Mode Console |

SOLUTION SYSTEM:

| | | |
|---------------------|------------------------|------------------------|
| Solution Tank Cap.: | 10 gallons (38 liters) | 10 gallons (38 liters) |
| Solution Flow Rate: | 0 - .5 gpm (0 - 2 lpm) | 0 - .5 gpm (0 - 2 lpm) |
| Solution Filter: | Stainless / Inline | Stainless / Inline |

RECOVERY SYSTEM:

| | | |
|--------------------------------|--------------------------------|--------------------------------|
| Recovery Tank Cap.: | 10 gallons (38 liters) | 10 gallons (38 liters) |
| Vac. Power: | 0.75 hp (559 watts) | 0.75 hp (559 watts) |
| Drain Hose: | 1.5" diameter (4 cm) | 1.5" diameter (4 cm) |
| Vacuum Specs (lift / airflow): | 70" / 70 cfm (178 cm / 21 cmm) | 70" / 70 cfm (178 cm / 21 cmm) |
| Demisting Chamber: | 1.25 gallons (5 liters) | 1.25 gallons (5 liters) |
| Drain Saver: | 30 cubic inches (70 cubic cm) | 30 cubic inches (70 cubic cm) |

GENERAL:

| | | |
|--------------------------------|--|--|
| Cleaning Width: | 17-BD: 17" (43 cm) 20-BD: 20" (51 cm) | 17-D: 17" (43 cm) 20-D: 20" (51 cm) |
| Cleaning Rate/Hour (Sq.Ft/Hr): | Up to 18,474 (5,631 m) | Up to 20,525 (6,256 m) |
| Sound Level: | 67 dBA | 67 dBA |

DRIVE SYSTEM:

| | | |
|-----------------|------------|---------------------------------------|
| Standard Drive: | Pad Assist | 0.4 hp (298 watts), all gear / sealed |
| Forward Speed: | NA | 0-230 ft/min (4 mph) (6 kph) |
| Reverse Speed: | NA | 0-130 ft/min (2 mph) (3 kph) |

RPS CORPORATION

P.O. Box 368
Racine, WI 53401
Phone: (800) 634-4060
Fax: (866) 901-3335

© RPS Corporation 2011.
All Rights Reserved.

Since our policy is one of constant improvement,
all specifications are subject to change without notice.

AUTHORIZED DISTRIBUTOR